## NSN 5306-01-078-2920

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-078-2920

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.960 inches
Fastener Length:
1.530 inches
Head Style:
Spline extended washer
Head Height:
0.348 inches
Width Between Flats:
Between 0.644 inches and 0.651 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
0.102 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
0.570 inches
Hole Quantity:
4 Hala Types
Hole Type:  Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Round
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams5663 assn standard single material response
7.11.0 0002 doon olandard olingio material response of amboode assit standard single material response

## NSN 5306-01-078-2920

Shear Bolt - Page 2 of 2



Precious Material And Location:
silver
Precious Material:
Silver
Surface Treatment:
Silver
Surface Treatment Specification:
Qq-s-365, type 1 gr b federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0