

View Online at <https://aerobasegroup.com/nsn/5306-01-078-8926>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.350 inches and 0.390 inches

**Fastener Length:**

Between 0.490 inches and 0.510 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**Hole Diameter:**

Between 0.060 inches and 0.075 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.120 inches and 0.140 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Nonstandard Thread Pitch Diameter:**

+0.1644/+0.1664 inches

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard 1st material response or ams7478 assn standard 2nd material response

**Precious Material And Location:**

silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams2410 assn standard single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0