NSN 5306-01-079-1362

Shear Bolt - Page 1 of 2

Between 0.813 inches and 0.863 inches

Between 2.948 inches and 2.978 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Double hexagon w/hole

Head Style:

За



View Online at https://aerobasegroup.com/nsn/5306-01-079-1362

Head Height:
Between 0.494 inches and 0.514 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
Between 0.113 inches and 0.133 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 2.115 inches and 2.135 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Steel comp xm-12
Material Specification:
Ams 5862 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5306-01-079-1362

Shear Bolt - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0