

View Online at <https://aerobasegroup.com/nsn/5306-01-079-1363>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.887 inches and 0.937 inches

**Fastener Length:**

Between 2.585 inches and 2.615 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.608 inches and 0.628 inches

**Width Between Flats:**

Between 0.679 inches and 0.690 inches

**Extended Washer Diameter:**

Between 1.040 inches and 1.050 inches

**Extended Washer Thickness:**

Between 0.140 inches and 0.160 inches

**Grip Diameter:**

Between 0.6235 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.678 inches and 1.698 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.331 inches first hole and 2.371 inches first hole

**Material:**

Stainless steel

**Material Specification:**

23-112, ty a, fscm 76301 mfr ref single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0