

View Online at <https://aerobasegroup.com/nsn/5306-01-079-1363>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.887 inches and 0.937 inches

Fastener Length:

Between 2.585 inches and 2.615 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.608 inches and 0.628 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

Between 0.140 inches and 0.160 inches

Grip Diameter:

Between 0.6235 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 1.678 inches and 1.698 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.331 inches first hole and 2.371 inches first hole

Material:

Stainless steel

Material Specification:

23-112, ty a, fscm 76301 mfr ref single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0