

View Online at <https://aerobasegroup.com/nsn/5306-01-079-1364>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.742 inches and 0.792 inches

**Fastener Length:**

Between 6.252 inches and 6.282 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.494 inches and 0.514 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Extended Washer Diameter:**

Between 0.818 inches and 0.828 inches

**Extended Washer Thickness:**

Between 0.113 inches and 0.133 inches

**Grip Diameter:**

Between 0.4990 inches and 0.4995 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 5.490 inches and 5.510 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

6.006 inches first hole and 6.046 inches first hole

**Material:**

Stainless steel

**Material Specification:**

23-112, ty a, fscm 76301 mfr ref single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0