NSN 5306-01-079-5148

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-079-5148

-
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.721 inches and 0.761 inches
Fastener Length:
Between 2.981 inches and 3.001 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.425 inches and 0.445 inches
Width Between Flats:
Between 0.490 inches and 0.510 inches
Extended Washer Diameter:
Between 0.740 inches and 0.750 inches
Extended Washer Thickness:
Between 0.089 inches and 0.109 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 2.240 inches and 2.260 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
2 1 1 23.55

NSN 5306-01-079-5148

Shear Bolt - Page 2 of 2

Fiig: A003b0



Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No