

View Online at <https://aerobasegroup.com/nsn/5306-01-079-7245>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.673 inches and 0.703 inches

**Fastener Length:**

Between 4.985 inches and 5.015 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.615 inches and 0.625 inches

**Head Height:**

0.343 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.3755 inches and 0.3785 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.781 inches first hole

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-200/3 temper t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 type 1 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-a-8625 spec.