

View Online at <https://aerobasegroup.com/nsn/5306-01-080-6603>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.812 inches and 0.872 inches

**Fastener Length:**

Between 5.577 inches and 5.607 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.281 inches and 0.297 inches

**Width Between Flats:**

Between 0.741 inches and 0.751 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 4.735 inches and 4.765 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.549 inches first hole and 5.569 inches first hole

**Product Name:**

Navy special project

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1008 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0