## NSN 5306-01-080-9149

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-080-9149

| View Offiline at https://defobasegroup.com/hish/55000-01-000-51-45                               |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.514 inches and 0.574 inches  |
| Fastener Length:   |
| Between 4.154 inches and 4.184 inches  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 0.156 inches and 0.172 inches  |
| Width Between Flats:   |
| Between 0.430 inches and 0.439 inches  |
| Hole Diameter:   |
| Between 0.046 inches and 0.056 inches  |
| Thread Diameter:   |
| 0.250 inches   |
| Grip Length:   |
| Between 3.610 inches and 3.640 inches  |
| Hole Quantity:   |
| 1  |
| Hole Type:   |
| Drilled  |
| Features Provided:   |
| Finished head  |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Hole Configuration Style:  |
| Hexagon flats  |
| Product Name:  |
| Navy special project   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5731 assn standard single material response or ams5732 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unjf   |

## NSN 5306-01-080-9149

Machine Bolt - Page 2 of 2



| Specific | ation | Data: |
|----------|-------|-------|
|----------|-------|-------|

80205-nas1004 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0