

View Online at <https://aerobasegroup.com/nsn/5306-01-080-9188>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.268 inches and 0.318 inches

**Fastener Length:**

Between 1.216 inches and 1.246 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.154 inches and 0.174 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2483 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.075 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.928 inches and 0.948 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.103 inches first hole and 1.133 inches first hole

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Navy special project

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0