## NSN 5306-01-081-6110

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-081-6110

View Online at https://aerobasegroup.com/nsn/5306-01-081-6110
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.625 inches and 0.665 inches
Fastener Length:
Between 4.510 inches and 4.530 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.428 inches and 0.448 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 3.865 inches and 3.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-081-6110

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0