## NSN 5306-01-083-1595

Machine Bolt - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-01-083-1595

| View Online at https://aerobasegroup.com/nsn/5306-01-083-1595          |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.125 inches   |
| Fastener Length:   |
| Between 1.690 inches and 1.750 inches                                  |
| Head Style:  |
| Distorted head   |
| Head Height:   |
| Between 0.281 inches and 0.291 inches                                  |
| Width Between Flats:   |
| Between 0.612 inches and 0.625 inches                                  |
| Locking Feature:   |
| Distortions bearing surface of head                                    |
| Thread Diameter:   |
| 0.438 inches   |
| Thready Qty Per Inch (tpi):  |
| 14   |
| Material:  |
| Steel  |
| Material Specification:  |
| Sae assn standard all material responses                               |
| Surface Treatment:   |
| Phosphate  |
| Surface Treatment Specification:                                       |
| Mil-p-16232 ty z cl 2 military specification single treatment response |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |
| Mil-std (military Standard):   |
| Mil-p-16232 spec.  |
|  |