

View Online at <https://aerobasegroup.com/nsn/5306-01-084-0233>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.359 inches and 0.438 inches

Fastener Length:

Between 0.500 inches and 0.547 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

Width Between Flats:

Between 0.365 inches and 0.377 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.1090 inches and 0.141 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Special Features:

Furnished with tab 2024-t4 al alloy; spacer 4130 steel, cadmium plated; washer cres

Material:

Steel comp 4140 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0