

View Online at <https://aerobasegroup.com/nsn/5306-01-084-1158>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.710 inches and 1.150 inches

Fastener Length:

Between 1.210 inches and 1.250 inches

Head Style:

Distorted head

Head Height:

Between 0.125 inches and 0.135 inches

Width Between Flats:

Between 0.428 inches and 0.438 inches

Locking Feature:

Distortions top of head

Thread Diameter:

0.250 inches

Grip Length:

Between 0.100 inches and 0.500 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Mil-p-16232 ty z cl 2 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.