## NSN 5306-01-085-3227

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-085-3227

View Online at https://aerobasegroup.com/nsn/5306-01-085-3227
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.492 inches and 0.532 inches
Fastener Length:
Between 2.627 inches and 2.647 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.310 inches
Width Between Flats:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
Between 0.059 inches and 0.079 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 2.115 inches and 2.135 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-085-3227

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0