
## NSN 5306-01-085-6754

Shear Bolt - Page 1 of 2



AeroBase Group

## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.510 inches and 0.560 inches

### Fastener Length:

Between 1.145 inches and 1.175 inches

### Head Style:

Spline extended washer

## Head Height:

Between 0.194 inches and 0.234 inches

## **Extended Washer Diameter:**

Between 0.460 inches and 0.470 inches

## **Extended Washer Thickness:**

Between 0.026 inches and 0.046 inches

### **Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

### Head Minor Diameter:

Between 0.318 inches and 0.324 inches

## Thread Diameter:

0.250 inches

Grip Length:

Between 0.615 inches and 0.635 inches

## Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

260000 pounds per square inch

## Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

#### Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

## **Material Specification:**

Ams 6487 assn standard single material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

## Thread Series Designator:

Unjf

# NSN 5306-01-085-6754

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-8837 spec.

