## NSN 5306-01-087-1078

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-087-1078 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.340 inches **Fastener Length:** 4.380 inches **Head Style:** Hexagon **Head Height:** 0.620 inches Width Between Flats: 1.250 inches **First Diameter From Head:** Between 0.860 inches and 0.870 inches **Second Diameter From Head:** Between 0.610 inches and 0.620 inches **Third Diameter From Head:** Between 0.400 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.880 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.880 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 4.040 inches **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 32.0 rockwell c and 36.0 rockwell c **Externally Relieved Body Diameter Quantity:** 3 Material: Steel **Material Specification:** Astm-a322 assn standard single material response and astm-a331 assn standard single material response **Surface Treatment:** Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 3 federal specification single treatment response

## NSN 5306-01-087-1078

Externally Relieved Body Bolt - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf                       |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |
| Demilitarization:         |
| No                        |
| Fiig:                     |

A003b0