

<b>NSN 5306-01-090-8613</b> Machine Bolt - Page 1 of 2	ACTUBASE Group
View Online at https://aerobasegroup.com/nsn/5306-01-090-8613	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.740 inches and 0.820 inches	
Fastener Length:	
Between 1.865 inches and 1.885 inches	
Head Style:	
Double hexagon w/hole	
Head Height:	
Between 0.320 inches and 0.340 inches	
Width Between Flats:	
Between 0.304 inches and 0.313 inches	
Extended Washer Diameter:	
0.438 inches	
Extended Washer Thickness:	
Between 0.060 inches and 0.070 inches	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 1.065 inches and 1.125 inches	
Features Provided:	
Finished head	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
1250000 pounds per square inch	
Hardness Rating:	
26.0 rockwell c and 32.0 rockwell c	
Surface Finish:	
63.0 microinches grip	
Metavial	

# Material:

Steel comp 8740

# **Material Specification:**

Ams 6322 assn standard single material response

#### **Surface Treatment:**

Oxide

# **Surface Treatment Specification:**

Ams 2485 assn standard single treatment response

### **Thread Series Designator:**

Unf

# NSN 5306-01-090-8613

Machine Bolt - Page 2 of 2



		fe	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0