NSN 5306-01-091-6905

Shear Bolt - Page 1 of 2

Between 1.000 inches and 1.050 inches

Between 2.510 inches and 2.540 inches

Thread Class:

Right-hand

Thread Direction:

Thread Length:

Fastener Length:

Head Style:

За



View Online at https://aerobasegroup.com/nsn/5306-01-091-6905

Spline extended washer **Head Height:** Between 0.495 inches and 0.515 inches Width Between Flats: Between 0.711 inches and 0.717 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.102 inches and 0.122 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 military specification single treatment response **Thread Series Designator:** Unjf

NSN 5306-01-091-6905

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Shelf Life:

Mil-std (military Standard): Mil-c-8837 spec.