

View Online at <https://aerobasegroup.com/nsn/5306-01-092-0214>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.803 inches and 0.853 inches

**Fastener Length:**

Between 2.563 inches and 2.593 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.291 inches and 0.331 inches

**Width Between Flats:**

Between 0.514 inches and 0.521 inches

**Extended Washer Diameter:**

Between 0.740 inches and 0.750 inches

**Extended Washer Thickness:**

Between 0.072 inches and 0.092 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.740 inches and 1.760 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Product Name:**

Navy special project

**Special Features:**

Color white

**Material:**

Steel comp 8740 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Paint top of head

**Surface Treatment Specification:**

Tt-e-489 no. 17875 federal specification single treatment response top of head

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.