

View Online at <https://aerobasegroup.com/nsn/5306-01-092-4215>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.723 inches and 0.823 inches

Fastener Length:

Between 2.820 inches and 2.850 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.393 inches and 0.403 inches

Width Between Flats:

Between 0.485 inches and 0.500 inches

Extended Washer Diameter:

Between 0.740 inches and 0.750 inches

Extended Washer Thickness:

Between 0.082 inches and 0.092 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 1.750 inches and 1.760 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Special Features:

Color blue

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Paint top of head

Surface Treatment Specification:

Tt-e-489 number 15102 federal specification single treatment response top of head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.