## NSN 5306-01-092-4216

Shear Bolt - Page 1 of 2

Between 0.949 inches and 1.060 inches

Between 2.820 inches and 2.850 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

Double hexagon w/hole

**Head Style:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-092-4216

Head Height:
Between 0.552 inches and 0.572 inches
Width Between Flats:
Between 0.673 inches and 0.688 inches
Extended Washer Diameter:
Between 1.040 inches and 1.050 inches
Extended Washer Thickness:
Between 0.113 inches and 0.133 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 1.750 inches and 1.760 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Special Features:
Color blue
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Paint top of head
Surface Treatment Specification:
Tt-e-489 number 15102 federal specification single treatment response top of head

## NSN 5306-01-092-4216

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-8837 spec.