NSN 5306-01-092-5478

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-092-5478

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.710 inches and 0.760 inches |
| Fastener Length: |
| Between 6.470 inches and 6.500 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.250 inches and 0.265 inches |
| Width Between Flats: |
| Between 0.741 inches and 0.752 inches |
| Grip Diameter: |
| Between 0.4985 inches and 0.4995 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| Between 5.740 inches and 5.760 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Surface Finish: |
| 63.0 microinches grip |
| Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 6150 or steel comp 8735 or steel comp 8740 |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416 type 1 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1308 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5306-01-092-5478

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0