## NSN 5306-01-092-5478

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-092-5478

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.710 inches and 0.760 inches
Fastener Length:
Between 6.470 inches and 6.500 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 5.740 inches and 5.760 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
63.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 1 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1308 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-092-5478

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0