Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-092-6940

3a         Thread Direction:         Right-hand         Fastener Length:         4.404 inches         Head Style:         Dee chamfer         Head Diameter:         Between 0.430 inches and 0.440 inches         Head Jameter:         Between 0.351 inches and 0.361 inches         Distance From Centriline To Flat:         Between 0.351 inches and 0.361 inches         Distance From Centriline To Flat:         Between 0.250 inches and 0.254 inches         First Diameter From Head:         0.294 inches         Thred Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.722 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.720 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surfac	Thread Class:
Thread Direction:         Right-hand         Fastener Longth:         4.404 inches         Head Style:         Dee chamfer         Head Diameter:         Between 0.430 inches and 0.440 inches         Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centretine To Flat:         Between 0.151 inches and 0.254 inches         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         Between 0.250 inches and 0.254 inches         Forth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.291 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.712 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.720 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.720 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.720 in	
Right-hand         Fastener Length:         4.404 inches         Head Style:         Dee chamfer         Head Diameter:         Between 0.430 inches and 0.440 inches         Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         D.294 inches         Point Diameter From Head:         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         D.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.728 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of F	
Azesener Length:         4.404 inches         Head Style:         Dee chamfer         Head Diameter:         Between 0.430 inches and 0.440 inches         Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Third Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.672 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.892 inches         Thread Diameter:         0.291 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.892 inches	
A 404 inches Head Style: Dee chamfer Head Diameter: Between 0.430 inches and 0.440 inches Head Height: Between 0.351 inches and 0.361 inches Distance From Centerline To Flat: Between 0.351 inches and 0.361 inches Distance From Centerline To Flat: Between 0.151 inches and 0.155 inches First Diameter From Head: Between 0.250 inches and 0.254 inches Second Diameter From Head: 0.294 inches Third Diameter From Head: 0.294 inches Fourth Diameter From Head: 0.294 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.672 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.892 inches Thread Diameter: 3.892 inches Thread Diameter: 3.892 inches Thread Diameter: 3.892 inches Thread Diameter: 3.892 inches Thread Diameter: 3.892 inches Thread Series Designator: 4 Thread Series Designator: Unif	-
Head Style:         Dee chamfer         Head Diameter:         Between 0.430 inches and 0.440 inches         Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         0.472 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.728 inches         Thread Diameter:         0.250 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: <td>-</td>	-
Dee chamfer         Head Diameter:         Between 0.430 inches and 0.440 inches         Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.472 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.728 inches         Thread Diameter:         0.250 inches         Thread Vier Inch (tpi):	
Head Diameter:         Between 0.430 inches and 0.440 inches         Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Third Diameter From Head:         0.294 inches         Potter Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.472 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.472 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         <	-
Between 0.430 inches and 0.440 inches         Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Third Diameter From Head:         0.294 inches         Pourth Diameter From Head:         0.294 inches         Pourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.721 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.4250 inches         Thready Up Per Inch (tpi):         28         Externally Relieved Body Diameter Quantity:         4         Thread Series Designator:         Unif         Shelf Life:	
Head Height:         Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Third Diameter From Head:         0.294 inches         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Fourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.672 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.672 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         0.250 inches         Thread Diameter:         0.250 inches         Thready Qty Per Inch (tpi):         28         Externally Relieved Body Diameter Quantity:         4         Thread Series Designator:	
Between 0.351 inches and 0.361 inches         Distance From Centerline To Flat:         Between 0.151 inches and 0.155 inches         First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Third Diameter From Head:         0.294 inches         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.672 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         3.692 inches         Thread Diameter:         0.250 inches         Thready Qty Per Inch (tpi):         28         Externally Relieved Body Diameter Quantity:         4         Thread Series Designator:         Unjf         Shelf Life:	
Distance From Centerline To Flat:Between 0.151 inches and 0.155 inchesFirst Diameter From Head:Between 0.250 inches and 0.254 inchesSecond Diameter From Head:0.294 inchesThird Diameter From Head:0.294 inchesBetween 0.250 inches and 0.254 inchesFourth Diameter From Head:0.294 inchesFourth Diameter From Head:0.294 inchesFourth Diameter From Head:0.294 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.672 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:1.722 inchesDistance From Largest Bearing Surface Of Head To End Of Third Diameter:2.718 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesThread Diameter:0.250 inchesThread Quy Per Inch (tpi):28Externally Relieved Body Diameter Quantity:4Thread Series Designator:UnjfShelf Life:	-
Between 0.151 inches and 0.155 inches First Diameter From Head: Between 0.250 inches and 0.254 inches Second Diameter From Head: 0.294 inches Third Diameter From Head: Between 0.250 inches and 0.254 inches Fourth Diameter From Head: 0.294 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.672 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.692 inches Thread Diameter: 0.250 inches Thread Diameter: 4 Thread Series Designator: Unjf Shelf Life:	
First Diameter From Head:         Between 0.250 inches and 0.254 inches         Second Diameter From Head:         0.294 inches         Third Diameter From Head:         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Fourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.672 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Third Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         3.692 inches         Thread Diameter:         0.250 inches         Thready Oty Per Inch (tpi):         28         Externally Relieved Body Diameter Quantity:         4         Thread Series Designator:         Unif         Shelf Life:	
Between 0.250 inches and 0.254 inchesSecond Diameter From Head:0.294 inchesThird Diameter From Head:Between 0.250 inches and 0.254 inchesFourth Diameter From Head:0.294 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.672 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:1.722 inchesDistance From Largest Bearing Surface Of Head To End Of Third Diameter:2.718 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:2.718 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesThread Diameter:0.250 inchesThready Oty Per Inch (tpi):28Externally Relieved Body Diameter Quantity:4Inread Series Designator:UnifShelf Life:	
Second Diameter From Head: 0.294 inches Third Diameter From Head: Between 0.250 inches and 0.254 inches Fourth Diameter From Head: 0.294 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.672 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 3.692 inches Thread Diameter: 0.250 inches Thread Diameter: 2.8 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	
0.294 inchesThird Diameter From Head:Between 0.250 inches and 0.254 inchesFourth Diameter From Head:0.294 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.672 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:1.722 inchesDistance From Largest Bearing Surface Of Head To End Of Third Diameter:2.718 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Externally Relieved Body Diameter Quantity:4Thread Series Designator:UnjfShelf Life:	
Third Diameter From Head:         Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.672 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.692 inches         Thread Diameter:         0.250 inches         Thready Qty Per Inch (tpl):         28         Externally Relieved Body Diameter Quantity:         4         Thread Series Designator:         Unjf         Shelf Life:	Second Diameter From Head:
Between 0.250 inches and 0.254 inches         Fourth Diameter From Head:         0.294 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.672 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         1.722 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         2.718 inches         Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:         3.692 inches         Thread Diameter:         0.250 inches         Thready Qty Per Inch (tpi):         28         Externally Relieved Body Diameter Quantity:         4         Thread Series Designator:         Unjf         Shelf Life:	
Fourth Diameter From Head:0.294 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.672 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:1.722 inchesDistance From Largest Bearing Surface Of Head To End Of Third Diameter:2.718 inchesDistance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Externally Relieved Body Diameter Quantity:4Thread Series Designator:UnjfShelf Life:	Third Diameter From Head:
0.294 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.672 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.692 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf	Between 0.250 inches and 0.254 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.672 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.692 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	Fourth Diameter From Head:
0.672 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.692 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	0.294 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.722 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.692 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
<ul> <li>1.722 inches</li> <li>Distance From Largest Bearing Surface Of Head To End Of Third Diameter:</li> <li>2.718 inches</li> <li>Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:</li> <li>3.692 inches</li> <li>Thread Diameter:</li> <li>0.250 inches</li> <li>Thready Qty Per Inch (tpi):</li> <li>28</li> <li>Externally Relieved Body Diameter Quantity:</li> <li>4</li> <li>Thread Series Designator:</li> <li>Unjf</li> <li>Shelf Life:</li> </ul>	0.672 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.692 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
2.718 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.692 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	1.722 inches
Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:3.692 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Externally Relieved Body Diameter Quantity:4Thread Series Designator:UnjfShelf Life:	Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
3.692 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	2.718 inches
Thread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Externally Relieved Body Diameter Quantity:4Thread Series Designator:UnjfShelf Life:	Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:
0.250 inches Thready Qty Per Inch (tpi): 28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	3.692 inches
Thready Qty Per Inch (tpi):   28   Externally Relieved Body Diameter Quantity:   4   Thread Series Designator:   Unjf   Shelf Life:	Thread Diameter:
28 Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	0.250 inches
Externally Relieved Body Diameter Quantity: 4 Thread Series Designator: Unjf Shelf Life:	Thready Qty Per Inch (tpi):
4 Thread Series Designator: Unjf Shelf Life:	28
Thread Series Designator: Unjf Shelf Life:	Externally Relieved Body Diameter Quantity:
Unjf Shelf Life:	4
Shelf Life:	Thread Series Designator:
	Unjf
N/a	Shelf Life:
	N/a
Unit Of Measure:	Unit Of Measure:

## NSN 5306-01-092-6940

Externally Relieved Body Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

