## NSN 5306-01-094-6057

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-094-6057



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.788 inches and 0.838 inches Fastener Length: Between 3.298 inches and 3.328 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches Grip Length: Between 2.490 inches and 2.510 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Steel comp h11 **Material Specification:** 

Ams 6487 assn standard single material response

## NSN 5306-01-094-6057

Shear Bolt - Page 2 of 2

Surface Treatment: Nickel and cadmium and chromate Surface Treatment Specification: Ams 2416 assn standard single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A003b0

