Externally Relieved Body Bolt - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-01-095-4610

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.445 inches and 0.475 inches
Fastener Length:
Between 1.302 inches and 1.322 inches
Head Style:
Double hexagon w/hole
Head Height:
0.422 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
0.562 inches
Extended Washer Thickness:
Between 0.090 inches and 0.100 inches
First Diameter From Head:
Between 0.290 inches and 0.293 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.827 inches and 0.877 inches
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
42.0 rockwell c and 46.0 rockwell c
Externally Relieved Body Diameter Quantity:
1
Product Name:
Navy special project
Material:
Steel comp 601
Material Specification:
Ams 6304 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924 cl 1 military specification single treatment response
Thread Series Designator:
Unjf

NSN 5306-01-095-4610

Externally Relieved Body Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.

