

View Online at <https://aerobasegroup.com/nsn/5306-01-095-4610>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.445 inches and 0.475 inches

**Fastener Length:**

Between 1.302 inches and 1.322 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.422 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

0.562 inches

**Extended Washer Thickness:**

Between 0.090 inches and 0.100 inches

**First Diameter From Head:**

Between 0.290 inches and 0.293 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.827 inches and 0.877 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

42.0 rockwell c and 46.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Navy special project

**Material:**

Steel comp 601

**Material Specification:**

Ams 6304 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 cl 1 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.