NSN 5306-01-096-1232

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-096-1232 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.400 inches **Fastener Length:** Between 1.360 inches and 1.390 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.240 inches and 0.250 inches **Head Height:** Between 0.128 inches and 0.148 inches **First Diameter From Head:** Between 0.136 inches and 0.137 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.990 inches and 1.010 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 **Surface Finish:** 32.0 microinches bearing surface of head **Special Features:** Dry film lubricant Material: Titanium alloy uns r56440 **Material Specification:** Nas 621 assn standard single material response **Surface Treatment:** Anodize

Unjc

Thread Series Designator:

NSN 5306-01-096-1232

Internal Wrenching Bolt - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0