## NSN 5306-01-096-7349

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-096-7349 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 1.516 inches and 1.546 inches **Head Style:** Hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.325 inches first hole and 1.375 inches first hole **Surface Finish:** 63.0 microinches grip Material: Titanium alloy **Material Specification:** Nas 621 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas675 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-096-7349

Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0