

View Online at <https://aerobasegroup.com/nsn/5306-01-097-9399>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.318 inches and 0.368 inches

Fastener Length:

Between 1.766 inches and 1.796 inches

Head Style:

Hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 1.428 inches and 1.448 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.641 inches first hole and 1.673 inches first hole

Surface Finish:

63.0 microinches bearing surface of head

Material:

Steel comp e4340 or steel comp 4140 or steel comp 6150 or steel comp 8735 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0