## NSN 5306-01-098-6783

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-098-6783 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.500 inches and 0.510 inches **Fastener Length:** 1.800 inches **Head Style:** Hexagon **Head Height:** Between 0.455 inches and 0.483 inches Width Between Flats: 1.120 inches Point Length: 1.110 inches **Point Diameter:** Between 0.623 inches and 0.624 inches **First Diameter From Head:** Between 0.605 inches and 0.620 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.190 inches and 0.200 inches **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 10 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 **Point Chamfer Angle:** 45.0 degrees Material: Steel **Material Specification:** Astm a322 assn standard single material response and astm a331 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5306-01-098-6783

Externally Relieved Body Bolt - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0