## NSN 5306-01-098-7775

Shear Bolt - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.428 inches and 0.478 inches

#### Fastener Length:

Between 3.438 inches and 3.468 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.250 inches and 0.265 inches

#### Width Between Flats:

Between 0.741 inches and 0.752 inches

#### Grip Diameter:

Between 0.4985 inches and 0.4995 inches

#### **Thread Diameter:**

0.500 inches

## Grip Length:

Between 2.990 inches and 3.010 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

## Surface Finish:

32.0 microinches threads

## Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416 type 1 cl 3 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas1108 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-098-7775

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

