NSN 5306-01-100-2024

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-100-2024

View Online at https://aerobasegroup.com/nsn/5306-01-100-2024
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.312 inches and 0.481 inches
Fastener Length:
Between 3.202 inches and 3.340 inches
Head Style:
Hexagon
Head Height:
Between 0.078 inches and 0.110 inches
Width Between Flats:
Between 0.365 inches and 0.377 inches
Grip Diameter:
Between 0.1885 inches and 0.1894 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 2.859 inches and 2.891 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Surface Treatment Specification:
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator:
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas464 professional/industrial association standard
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas464 professional/industrial association standard Shelf Life:

--

NSN 5306-01-100-2024

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0