

View Online at <https://aerobasegroup.com/nsn/5306-01-101-6023>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.309 inches and 0.359 inches

Fastener Length:

Between 0.756 inches and 0.786 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.265 inches and 0.285 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.340 inches and 0.350 inches

Extended Washer Thickness:

Between 0.054 inches and 0.074 inches

Hole Diameter:

Between 0.032 inches and 0.042 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.427 inches and 0.447 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0