

View Online at <https://aerobasegroup.com/nsn/5306-01-102-0306>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.926 inches

**Fastener Length:**

2.051 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.530 inches

**Width Between Flats:**

Between 0.616 inches and 0.627 inches

**Extended Washer Diameter:**

Between 0.940 inches and 0.950 inches

**Extended Washer Thickness:**

0.098 inches

**Hole Diameter:**

0.070 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Thread Diameter:**

0.500 inches

**Grip Length:**

1.125 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Sps-m-573 fscm 56878 military standard single material response

**Thread Series Designator:**

Unf

**Specification Data:**

56878-ewb-26 manufacturers standard

**Purchase Description Identification:**

56878-sps-b-71320

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0