NSN 5306-01-102-1863

Shear Bolt - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5306-01-102-1863

Thread Direction:				
Right-hand				
Thread Length:				
Between 0.733 inches and 0.783 inches				
Fastener Length:				
Between 2.368 inches and 2.398 inches				
Head Style:				
Double hexagon extended washer				
Head Height:				
Between 0.327 inches and 0.347 inches				
Width Between Flats:				
Between 0.423 inches and 0.438 inches				
Extended Washer Diameter:				
Between 0.639 inches and 0.649 inches				
Extended Washer Thickness:				
Between 0.059 inches and 0.079 inches				
Grip Diameter:				
Between 0.3735 inches and 0.3745 inches				
Thread Diameter:				
0.375 inches				
Grip Length:				
Between 1.615 inches and 1.635 inches				
Thready Qty Per Inch (tpi):				
24				
Min. Tensile Strength (psi):				
220000 pounds per square inch				
Hardness Rating:				
46.0 rockwell c and 50.0 rockwell c				
Material:				
Steel comp h11				
Material Specification:				
Ams6487 assn standard single material response				
Surface Treatment:				
Cadmium and chromate				
Surface Treatment Specification:				
Mil-c-8837, type 2cl 2 military specification single treatment response				
Thread Series Designator:				
Unjf				
Shelf Life:				
N/a				

NSN 5306-01-102-1863

Shear Bolt - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.