

View Online at <https://aerobasegroup.com/nsn/5306-01-102-1863>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.733 inches and 0.783 inches

Fastener Length:

Between 2.368 inches and 2.398 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.327 inches and 0.347 inches

Width Between Flats:

Between 0.423 inches and 0.438 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.059 inches and 0.079 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.