

View Online at <https://aerobasegroup.com/nsn/5306-01-102-1864>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.298 inches and 0.348 inches

**Fastener Length:**

Between 2.183 inches and 2.213 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Hole Diameter:**

Between 0.046 inches and 0.056 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.865 inches and 1.885 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Hexagon corners

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard 1st material response or ams5737 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6303 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0