

View Online at <https://aerobasegroup.com/nsn/5306-01-102-5181>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.715 inches and 0.775 inches

Shank Length:

1.245 inches

Thread Diameter:

0.4375 inches

Thready Qty Per Inch (tpi):

20

Special Features:

0.106 in. Diameter hole drilled 0.197 in. From shank end

Material:

Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 2 class 3 federal specification 1st treatment response or qq-z-325 type 2 class 3 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1251 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.