

View Online at <https://aerobasegroup.com/nsn/5306-01-103-2551>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.469 inches

Fastener Length:

Between 0.642 inches and 0.672 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.311 inches and 0.312 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.178 inches and 0.198 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c fastener and 40.0 rockwell c fastener

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener

Material Specification:

Mil-s-5000 military specification 1st material response fastener or mil-s-5626 military specification 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener or mil-s-6098 military specification 4th material response fastener or mil-s-8503 military specification 5th material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas1225 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.