## NSN 5306-01-105-7207

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-105-7207

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.455 inches and 0.505 inches
Fastener Length:
Between 2.027 inches and 2.057 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.338 inches and 0.358 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.072 inches and 0.092 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.552 inches and 1.572 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c

**Hole Configuration Style:** 

Double hexagon longitudinal hole

Material:

Steel comp h11

**Material Specification:** 

Ams 6485 assn standard single material response

## NSN 5306-01-105-7207

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: