

View Online at <https://aerobasegroup.com/nsn/5306-01-106-8238>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.320 inches and 0.370 inches

**Fastener Length:**

Between 0.518 inches and 0.548 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.178 inches and 0.198 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-6603 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.