Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-107-3504

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.889 inches |
| Fastener Length: |
| 2.000 inches |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| 0.561 inches |
| Width Between Flats: |
| 0.625 inches |
| Extended Washer Diameter: |
| 0.875 inches |
| Extended Washer Thickness: |
| 0.130 inches |
| Thread Diameter: |
| 0.562 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 18 |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams2400 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5306-01-107-3504

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

