
## NSN 5306-01-107-4144

Machine Bolt - Page 1 of 2

**Thread Class:** 





3a **Thread Direction: Right-hand Thread Length:** Between 0.740 inches and 0.820 inches Fastener Length: Between 1.178 inches and 1.198 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** 0.060 inches Hole Diameter: 0.065 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.378 inches and 0.438 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material:

Steel comp 8740

## NSN 5306-01-107-4144

Machine Bolt - Page 2 of 2



Material Specification: Ams6322 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams2400 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0