

View Online at <https://aerobasegroup.com/nsn/5306-01-108-2238>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.365 inches and 0.385 inches

**Fastener Length:**

Between 1.305 inches and 1.345 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.172 inches

**Width Between Flats:**

Between 0.430 inches and 0.440 inches

**Shoulder Diameter:**

0.3115 inches first shoulder and 0.3120 inches first shoulder

**Shoulder Length:**

0.940 inches first shoulder and 0.960 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.155 inches first hole and 1.175 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0