## NSN 5306-01-108-2520

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-108-2520



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.828 inches and 0.878 inches

#### Fastener Length:

Between 3.338 inches and 3.368 inches

#### Head Style:

Spline extended washer

#### Head Height:

Between 0.440 inches and 0.460 inches

#### **Extended Washer Diameter:**

Between 0.922 inches and 0.932 inches

#### **Extended Washer Thickness:**

Between 0.047 inches and 0.077 inches

#### **Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

#### Head Minor Diameter:

Between 0.644 inches and 0.651 inches

### Thread Diameter:

0.500 inches

Grip Length:

Between 2.490 inches and 2.510 inches

#### Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

#### Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

#### Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

#### **Material Specification:**

Ams6487 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Mil-c-8837, type 2, class 2 military specification single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5306-01-108-2520

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-8837 spec.

