## NSN 5306-01-108-7462

Shear Bolt - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-108-7462

oa
Thread Direction:
Right-hand
Thread Length:
Between 0.531 inches and 0.581 inches
Fastener Length:
Between 0.853 inches and 0.883 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.383 inches and 0.389 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Round
Surface Finish:
32.0 microinches grip
Material:
041 4440 4040

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

## NSN 5306-01-108-7462

Shear Bolt - Page 2 of 2

No Fiig: A003b0



Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response $$
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: