

View Online at <https://aerobasegroup.com/nsn/5306-01-109-7463>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.445 inches

Fastener Length:

3.790 inches

Head Style:

Round w/wrench flats chamfered

Head Diameter:

1.060 inches

Head Height:

0.270 inches

Width Between Flats:

0.880 inches

Shoulder Diameter:

Between 0.7490 inches and 0.7495 inches

Shoulder Length:

Between 3.270 inches and 3.280 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Concentric Hole Depth:

3.000 inches

Concentric Hole Diameter:

0.375 inches

Thread Diameter:

0.562 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

280000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.650 inches first hole

Material:

Steel

Material Specification:

Mil-s-8844 cl 3 cond e-2 military specification single material response

Surface Treatment:

Chromium grip

Surface Treatment Specification:

Stf1139 fscm 76301 mfr ref single treatment response grip

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8844 spec.